



TR 900

Height Adjustable Bathtub

Hygiene Equipment
Designed for People

TR 900

The friendly functional design of the TR 900 integrated bathtub and panel, makes it simple and convenient to operate. The smooth and soft design also makes it easy to clean and maintain.



Registered at Medical Products Agency, Sweden as a MDR Class 1 product according to MDR 2017/745.

TR reserves the right to make design changes and/or improvements without notice.



The TR 900 Whirlpool models improves the patient's wellbeing. The relaxing whirlpool effect stimulates the circulation and assists in washing the patient.

The TR 900 Autofill bath models are even more simple and efficient for the staff to use. No waiting or observation time when prefilling the bathtub.





TR 900

Height Adjustable Bathtub

Hygiene Equipment
Designed for People

- The 3/4" (22 mm) thermostatic mixing valve, the 3/4" internal piping and the double filling spouts give a good water flow and short filling time.
- The digital LED thermometer shows the shower and bathtub filling water temperature and the Autofill models also show the still water temperature in the bathtub.
- The cleaning system with yellow hose (see picture) is mixed with cold water to minimize inhalation of the cleaning mixture, which is pre-set at the factory to avoid unnecessary alteration.
- Unique whirlpool inlet cleaning adapter. The whirlpool bath models allow you to regulate both jet direction and the quantity of air.
- The extra width at the head end allows more space for arms and shoulders, and is an advantage when cleaning the upper body. The double layered bathtub minimizes heat loss. TR 900 is delivered with an adjustable foot support as standard.

Integrated with the TR9650 mobile patient Combilift, the system provides a safe moving and handling for both patients and attendant. During the bathing cycle the client never leaves the comfort and security of the chair or stretcher.



Specifications

Length	2325 mm / 92"
Width	830 mm / 33"
Typical lift speed, no load	11 mm/s
Working load limit	150 kg / 330 lbs
Operation height range	610-940 mm / 24" - 37"
Power supply	230 V, 50Hz / 110 V, 60 Hz
Overall weight (empty)	265 kg / 584 lbs

Bath models:

- TR 900 Standard
- TR 900 C Cleaning system
- TR 900 CW Cleaning and whirlpool system
- TR 900 A Autofill system
- TR 900 CA Cleaning and autofill system
- TR 900 CWA Cleaning, whirlpool and autofill system

Options/Accessories:

- Transport wheel beam and set of loading ramp
- Installation set TR 900, TR900 C/TR 900 CW
- Head pillow
- Local treatment in combination with Whirlpool.



TR 900 Autofill model



TR 900 Cleaning model



All TR 900 HiLo panels can be delivered with a stainless steel bathtub as an option. The stainless steel bathtub has the same functional design as the standard TR 900 glass fibre tub and is manufactured in high quality steel (EN 1.4301)

